



## LABORATORY GLASSWARE WASHER

Professional line - glassware washer 60 cm

- washing up to 95°C - antibacterial thermal disinfection
- electronic programming: 20 set programs + 10 free programs
- 3 microprocessors programmable electronic control
- serial port RS232 for connection to external printer or PC
- 128x64 pixel graphics display for different languages messages
- active thermodynamic drying
- alkaline powder detergent dispenser
- peristaltic pump for liquid neutralizer
- possibility of installing up to 3 additional peristaltic pumps
- washing chamber and internal door in AISI 316L stainless steel
- external panels made in AISI 304 stainless steel
- 2 independent washing levels through telescopic guides
- external dimensions LxWxH (mm) 600x640x850
- internal working dimensions LxWxH (mm) 520x515x545
- incorporated water softener with salt sensor
- cold water, hot water and demineralized water connections
- electronic door lock system for user safety
- electrical connection 3P+N 400V 50Hz 7kW max (switchable single-phase 230V)
- 60Hz version available
- without trolleys

Smeg S.p.A. Via Leonardo Da Vinci, 4 - 42016 Guastalla (RE) Italy - P. IVA 01555030350

Phone +39 0522 8211 - Fax +39 0522 821453 - [service.instruments@smeg.it](mailto:service.instruments@smeg.it)